

Main applications

Static and permanent structures
Inflatable structures



Highly translucent membrane

A durable lightweight membrane dedicated to internal use requiring a high level of natural light

Major advantages

- Highly Translucent: very high light transmission (48% regarding NFP 378.511) (consult us for applications in very sunny areas)

Technical specifications

Weight	490 g/m ² - EN ISO 2286-2
Standard format length	50 lm - 350 lm
Tensile strength (warp/weft)	230/220 daN/5 cm - EN ISO 1421
Tear strength (warp/weft)	20/20 daN - DIN 53.363
Adhesion	8 daN/5 cm
Finish	Varnish both sides
Flame retardancy	B-s2, d0 /EN 13501-1 — M2 /NFP 92.507 — B1 /DIN 4102-1 M2 /UNE 23.727 — BS 7837 — CSFMT19 — VKF 5.3 /SN 198898 Schwerbrennbar-Q1-TR1 /ONORM B3800-1 AS /NZS 1530.2 - 1530.3 — G1 /GOST30244-94
Warranty	10 years — Indoor use only
Maximum delivery time	In stock
Provided services	Jumbo rolls Cut length Slitting Length/width adjustment Short production runs Promised delivery guaranteed up to 1 000 lm

Precontraint®
Technology

2 colours

